

## Claims

[1] An optical system including an optically transparent member formed of crystalline material, characterized in that the direction of the fast axis relating to variation of birefringence of said optically transparent member when subjected to optical illumination is set to be substantially coincident with or substantially orthogonal to the direction of oscillation of the electrical field of linearly polarized light incident on said optically transparent member.

[2] Optical illumination equipment comprising an optical system according to claim 1, characterized in that the surface to be illuminated is illuminated with light through this optical system.

[3] Optical illumination equipment including an optically transparent member formed of crystalline material of the cubic system, wherein a surface to be illuminated is illuminated with light through this optically transparent member, characterized in that:

the direction of propagation of the light in said optically transparent member is set so as to be closer to the crystal orientation  $\langle 111 \rangle$  or crystal orientation  $\langle 100 \rangle$  than to crystal orientation  $\langle 110 \rangle$ .

[4] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises an optical member that is fixedly located in position in the optical path and the optical axis of said optical member is set so as to substantially coincide with the crystal orientation  $\langle 111 \rangle$  or crystal orientation  $\langle 100 \rangle$ .

[5] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises a prism and the input face and output

face of said prism are set so as to substantially coincide with the crystallographic plane {100}.

[6] The optical illumination equipment according to claim 3, characterized in that said optically transparent  
5 member comprises a prism and the input face and output face of said prism are set so as to substantially coincide with the crystallographic plane {111}.

[7] The optical illumination equipment according to claim 3, characterized in that said optically transparent  
10 member comprises a prism and one of the faces of the input face and output face of said prism is set to substantially coincide with the crystallographic plane {111} and the other face thereof is set to substantially coincide with the crystallographic plane {100} or the  
15 crystallographic plane {211}.

[8] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises a right-angled prism constituting an internal-face reflecting mirror and a reflecting face of  
20 said right-angled prism is set to substantially coincide with the crystallographic plane {100} and the plane defined by the optical axis of the input face of said right-angled prism and the optical axis of the output face of said right-angled prism is set so as to  
25 substantially coincide with the crystallographic plane {110}.

[9] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises a right-angled prism constituting an  
30 internal-face reflecting mirror and the reflecting face of said right-angled prism and the plane defined by the optical axis of the input face of said right-angled prism and the optical axis of the output face of said right-

angled prism are set to substantially coincide with the crystallographic plane {110}.

[10] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises a parallel planar plate for parallel displacement of a light ray that is incident along said optical axis, provided in said optical path in a manner capable of being tilted with respect to the optical axis and in that the optical axis of said parallel planar plate is set so as to substantially coincide with the crystal orientation  $\langle 100 \rangle$ .

[11] The optical illumination equipment according to claim 10, characterized in that said parallel planar plate is capable of being tilted in a direction from crystal orientation  $\langle 100 \rangle$  towards crystal orientation  $\langle 111 \rangle$ .

[12] The optical illumination equipment according to claim 3, characterized in that said optically transparent member comprises a parallel planar plate for parallel displacement of a ray incident along said optical axis, provided in said optical path in a manner capable of being tilted with respect to the optical axis and in that the optical axis of said parallel planar plate is set so as to substantially coincide with the crystal orientation  $\langle 111 \rangle$ .

[13] The optical illumination equipment according to claim 12, characterized in that said parallel planar plate is capable of being tilted from the crystal orientation  $\langle 111 \rangle$  towards the crystal orientation  $\langle 100 \rangle$ .

[14] (Amended) The optical illumination equipment according to claim 10, characterized in that said optically transparent member comprises a first parallel planar plate capable of being tilted about a first axis

and a second parallel planar plate capable of being tilted about a second axis substantially orthogonal to said first axis.

[15] (Amended) The optical illumination equipment  
5 according to claim 3, characterized in that the  
direction of the fast axis relating to variation of  
birefringence of said optically transparent member when  
subjected to optical illumination is set so as to be  
substantially coincident with or substantially orthogonal  
10 to the direction of oscillation of the electrical field  
of the linearly polarized light that is incident on said  
optically transparent member.

[16] (Amended) The exposure equipment comprising  
optical illumination equipment according to claim 2,  
15 characterized in that the pattern of a mask arranged at  
said surface to be illuminated is exposed onto a  
photosensitive substrate.

[17] (Amended) An exposure method, characterized in  
that a mask is illuminated through optical illumination  
20 equipment according to claim 2, and in that a pattern  
formed on said illuminated mask is exposed onto a  
photosensitive substrate